

Deuterium

1. Product and company identification

Product form : Substance
Name : Deuterium
CAS No : 7782-39-0
Formula : D2
Other means of identification : Heavy
Hydrogen

Manufacturer / Distributor:

Ehsan International Gases

40/9, Aurangabad, Nazimabad
#3, Karachi 74600, Pakistan.
+92 21 36612091 – 36612907

info@ehsan.com.pk

www.ehsan.com.pk

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial use. Use as directed.

Emergency telephone number

Emergency number : Onsite Emergency: 1-800-645-4633

2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Gas 1 H220
Compressed gas H280

Signal word (GHS-US) : DANGER
Hazard statements (GHS-US) : H220 - EXTREMELY FLAMMABLE GAS
H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF
HEATED OSHA-H01 - MAY DISPLACE OXYGEN AND CAUSE
RAPID SUFFOCATION. CGA-HG04 - MAY FORM EXPLOSIVE

Deuterium

MIXTURES WITH AIR CGA-HG08 - BURNS WITH INVISIBLE FLAME.

Precautionary statements (GHS-US) : P202 - Do not handle until all safety precautions have been read and understood

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

GHS04

- P210 - Keep away from heat, Open flames, sparks, hot surfaces. - No smoking
- P271+P403 - Use and store only outdoors or in a well-ventilated place.
- P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely
- P381 - Eliminate all ignition sources if safe to do so
- CGA-PG05 - Use a back flow preventive device in the piping.
- CGA-PG10 - Use only with equipment rated for cylinder pressure.
- CGA-PG12 - Do not open valve until connected to equipment prepared for use.
- CGA-PG06 - Close valve after each use and when empty.
- CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).

EN (English US) SDS ID: P-4585 1/8

This document is only controlled while on the Praxair, Inc. website and a copy of this controlled version is available for download.

2.3. Other hazards

Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.

2.4. Unknown acute toxicity (GHS-US)

Other hazards not contributing to the classification : None.

No data available

3: Composition/information on ingredients

3.2. Mixture

Name	Product identifier	%
Deuterium (Main constituent)	(CAS No) 7782-39-0	100

Deuterium

Not applicable

4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- First-aid measures after skin contact : Adverse effects not expected from this product.
- First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an ophthalmologist immediately.
- First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

None.

5.1. Extinguishing media

5: Firefighting measures

Suitable extinguishing media : Carbon dioxide, Dry chemical, Water spray or fog.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

- Fire hazard : EXTREMELY FLAMMABLE GAS. The hydrogen flame is nearly invisible. Hydrogen has a low ignition energy; escaping hydrogen gas may ignite spontaneously. A fireball forms if the gas cloud ignites immediately after release. Hydrogen forms explosive mixtures with air and oxidizing agents.
- Explosion hazard : EXTREMELY FLAMMABLE GAS. Forms explosive mixtures with air and oxidizing agents.
- Reactivity : No reactivity hazard other than the effects described in sub-sections below.

Firefighting instructions : If venting or leaking gas catches fire, do not extinguish flames. Flammable vapors may spread from leak, creating an explosive reignition hazard. Vapors can be ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static discharge, or other ignition sources at locations distant from product handling point. Explosive atmospheres may linger. Before entering an area, especially a confined area, check the atmosphere with an appropriate device.

Deuterium

Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart L—Fire Protection.

Protection during firefighting : Compressed gas: asphyxiant. Suffocation hazard by lack of oxygen.
 Special protective equipment for fire fighters : Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.

Specific methods Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas containers to rupture. Cool endangered containers with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.

6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : EXTREMELY FLAMMABLE GAS. Forms explosive mixtures with air and oxidizing agents. See section 5. Evacuate personnel to a safe area. Appropriate self-contained breathing apparatus may be required. Approach suspected leak area with caution. Remove all sources of ignition. if safe to do so. Reduce gas with fog or fine water spray. Stop flow of product if safe to do so. Ventilate area or move container to a well-ventilated area. Flammable gas may spread from leak. Before entering the area, especially a confined area, check the atmosphere with an appropriate device.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent waste from contaminating the surrounding environment. Prevent soil and water pollution. Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

6.3. Methods and material for containment and cleaning up

No additional information available

6.4. Reference to other sections

See also sections 8 and 13.

Deuterium

7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools. Use only explosion-proof equipment.

Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store only where temperature will not exceed 125°F (52°C). Post "No Smoking or Open Flames" signs in storage and use areas. There must be no sources of ignition. Separate packages and protect against potential fire and/or explosion damage following appropriate codes and requirements (e.g., NFPA 30, NFPA 55, NFPA 70, and/or NFPA 221 in the U.S.) or according to requirements determined by the Authority Having Jurisdiction (AHJ). Always secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand when the container is not in use. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods. For other precautions in using this product, see section 16.

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of

7.3. Specific end use(s)

an electrical circuit.

None.

Deuterium

8: Exposure controls/personal protection

8.2. Exposure controls

Deuterium (7782-39-0)	
ACGIH	Not established
USA OSHA	Not established

Appropriate engineering controls : An explosion-proof local exhaust system is acceptable. Local exhaust and general ventilation must be adequate to meet exposure standards. Mechanic (general) engineering controls: Use only in a closed system. Closed system, ventilation, explosion-proof electrical equipment and lighting.

Eye protection : Wear safety glasses with side shields.

Respiratory protection : An air-supplied respirator must be used while working with this product in confined spaces. The respiratory protection used must conform with OSHA rules as specified in 29 CFR 1910.134. Select per OSHA 29 CFR 1910.134 and ANSI Z88.2.

Thermal hazard protection : None necessary.

Other information : Consider the use of flame resistant anti-static safety clothing. Wear safety shoes while handling containers. Wear leather safety gloves and safety shoes when handling cylinders.

9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Molecular mass : 4 g/mol

Color : Colorless.

Odor : No data available

Odor threshold : No data available

pH : Not applicable.

Relative evaporation rate (butyl acetate=1) : No data available

Relative evaporation rate (ether=1) : Not applicable.

Melting point : -254 °C

Freezing point : No data available

Deuterium

Boiling point : -249.5 °C

Flash point : Not applicable.

Critical temperature : -234.9 K

Auto-ignition temperature : 585 °C

Decomposition temperature : No data available

Flammability (solid, gas) : 6.7 - 75 vol %

Vapor pressure : Not applicable.

Critical pressure : 1660 kPa

Relative vapor density at 20 °C : No data available

Relative density : 0.16

Relative gas density : 0.14

Solubility : Water: No data available

Log Pow : Not applicable.

Log Kow : Not applicable.

Viscosity, kinematic : Not applicable.

Viscosity, dynamic : Not applicable.

Explosive properties : Not applicable.

Oxidizing properties : None.

Explosive limits : No data available

9.2. Other information

Gas group : Compressed gas

Additional information : BURNS WITH INVISIBLE FLAME.

10: Stability and reactivity

10.1. Reactivity

Deuterium

No reactivity hazard other than the effects described in sub-sections below.

Stable under normal conditions.

10.2. Chemical stability

10.3. Possibility of hazardous reactions

May react violently with oxidants. Can form explosive mixture with air.

10.4. Conditions to avoid
10.5. Incompatible materials

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Oxidizing agent, Halogens, Alkaline earth metals; Alkaline earth metals, ductile metals; cold-worked ferrite steels.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Skin corrosion/irritation : Not classified pH:
Not applicable.

Serious eye damage/irritation : Not classified pH:
Not applicable.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Deuterium

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

12.1. Toxicity

12: Ecological information

Ecology - general : No ecological damage caused by this product.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Deuterium (7782-39-0)	
Persistence and degradability	Not applicable for inorganic gases.

Deuterium (7782-39-0)	
Log Pow	Not applicable.
Log Kow	Not applicable.
Bioaccumulative potential	No data available.

Deuterium (7782-39-0)	
Mobility in soil	No data available.
Ecology - soil	No ecological damage caused by this product.

Effect on ozone layer : None.

Effect on the global warming : No known effects from this product.

Deuterium

13: Disposal considerations

13.4. Mobility in soil

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

14: Transport information

In accordance with DOT

Transport document description : UN1957 Deuterium, compressed, 2.1
 UN-No.(DOT) : UN1957
 Proper Shipping Name (DOT) : Deuterium, compressed
 Department of Transportation (DOT) Hazard : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
 Classes
 Hazard labels (DOT) : 2.1 - Flammable gas



DOT Special Provisions (49 CFR 172.102) : N89 - When steel UN pressure receptacles are used, only those bearing the "H" mark are authorized.

Additional information

Emergency Response Guide (ERG) Number : 115 (including Deuterium)

Other information : No supplementary information available.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

Transport by sea

UN-No. (IMDG) : 1957
 Proper Shipping Name (IMDG) : DEUTERIUM, COMPRESSED
 Class (IMDG) : 2 - Gases
 MFAG-No : 115

Air transport

UN-No.(IATA) : 1957
 Proper Shipping Name (IATA) : Deuterium, compressed

Deuterium

Class (IATA) : 2
 Civil Aeronautics Law : Gases under pressure/Gases flammable under pressure

15: Regulatory information

15.2. International regulations

Deuterium (7782-39-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard Fire hazard

CANADA

Deuterium (7782-39-0)
Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Deuterium (7782-39-0)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

15.2.2. National regulations

Deuterium (7782-39-0)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Deuterium(7782-39-0)	
	U.S. - Pennsylvania - RTK (Right to Know) List

Deuterium

16: Other information

Revision date : 2/23/2015 12:00:00 AM
 Other information

: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture.

Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Praxair asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Praxair, Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair SDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Praxair sales representative, local distributor, or supplier, or download from www.praxair.com. If you have questions regarding Praxair SDSs, would like the document number and date of the latest SDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (Phone: 1-800-PRAXAIR/1-800-772-9247; Address: Praxair Call Center, Praxair, Inc., P.O. Box 44, Tonawanda, NY 14151-0044).

PRAXAIR and the Flowing Airstream design are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries.

NFPA health hazard : 0 - Exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials.
 NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.
 NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.

HMIS III Rating

Health : 0 Minimal Hazard - No significant risk to health

Deuterium

Flammability : 4 Severe Hazard
Physical : 3 Serious Hazard

SDS US (GHS HazCom 2012) - Praxair

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.